



Mini Joint Connector 3p Screw D7-13.5 IP68
THB.390.A1A



GENERAL INFORMATION

Type of installation	Joint connector (re-usable/re-accessible)
Product configuration	In-line connector
Colour	Black (Plastic components) - Techno green (Rubber components)
Overall dimensions (mm)	Ø 32.0 x 90.0

ELECTRIC DATA

No. connected cables	2
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	32A
Voltage rating (AC/DC)	450V AC
No. poles	3
Marking	L-N-E
Terminations	Screw
Terminations Thread/Tightening torque	M3 - max. 0.8 Nm

CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm ²)	0.50
Multi-stranded conductor cross-section without ferrule MAX (mm ²)	4.00
Solid conductor cross-section MIN (mm ²)	0.50
Solid conductor cross-section MAX (mm ²)	4.00
Conductor stripping length (mm)	30.00
Cable sheath stripping length (mm)	8.00
Recommened types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	7.00
Cable diameter MAX (mm)	13.50
Tightening torque of cable gland-connector	2.5 Nm
Tightening torque of nut-cable gland	2.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP68
	<i>*IP68 (50m/1h)</i>
IK rating	IK07
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 125°C
Proof Tracking Index (PTI)	PTI 250

MATERIALS

Exterior body	PA66 GF UL94 V0
Connector	PA66 GF UL94 V0
Cable gland	PA66 UL94 V2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

COMMERCIAL DATA

EAN	8057457093644
Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	43.20
Overall dimensions of box (mm)	400 x 400 x 230
Corresponding code in KIT	THR.390.S3D
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

INSTALLATIONS SHEET

Assembly instructions

File	Type	Size
 606001200_IST_I_TH390_400.pdf	PDF	1.48 MB

DRAWINGS

Drawings

File	Type	Size
 THB_390_AXA.pdf	PDF	291.94 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.