




LED Glow Economy

Type:

LED Panel Backlight

Application:

Office Lighting, Schools, Commercial Areas, Workshops, Hospitals



ADVANTAGES

- Light distributed directly. Using PMMA lens, so lighting effect is uniform and soft
- Driver – outside the body
- Option for built-in and surface mounting
- Cheaper price compared to other design.
- No LGP
- Quality in accordance to all EU standards and directives
- Energy Efficiency Class A+
- EU Made Product

ADVANTAGES OF ELECTROSTART

- EU Based Company
- Long experience in the field of Lighting and components
- Experience with customers in more than 40 countries
- Excellent Customer Service
- Projects based on Customer needs
- Products manufactured in EU
- Warranty on most products 5 Years

*** Luminous flux guaranteed at 25 ° ambient temperature.

ELECTRICAL CHARACTERISTICS

Supply voltage	220 - 240 VAC / 100 - 127 VAC
Frequency	50/60 Hz
Power factor	>0,9
Rated Power	36W/ 40W

LIGHTING CHARACTERISTICS

Efficiency	100/ 120 lm/W
Color rendering index (CRI)	>80
Flicker	Flicker free
Color temperature	3000K/ 4000K/ 6500 K

PROTECTION



Ingress protection	IP 40
Safety class	Class I

WARRANTY CONDITION

Lifespan	50 000 h
Warranty	5 Y
Working temperature	-10 ~40°C
Storage temperature	-20 ~60°C

OTHER INFORMATION

Material of Diffuser	PS
Body Material	Aluminium and Steel
Dimensions	595x595x35mm – D66, 1195x295x35mm –D312



ISO 9001
ISO 14001
ISO 45001
BUREAU VERITAS
Certification

