

## Module SLE G7 ADV

Modules SLE advanced



LES13 + LES15 with housing



LES21 with housing



LES09

### Product description

- \_ For spotlights and downlights
- \_ TIM variants for easy and fast assembly
- \_ For operating with SELV Driver suitable
- \_ Excellent thermal management by COB technology
- \_ Uniform radiation with Dam&Fill technology
- \_ Integrated LED module
- \_ Cooling required
- \_ Flexible operating mode
- \_ 4,100 K CRI90 module COI approved acc. to AS/NZS1680.2.5:1997
- \_ HE ... High Efficiency, NM ... Nominal Mode, HO ... High Output
- \_ Long lifetime: 55,000 hours
- \_ 5 years guarantee (conditions at

<https://www.tridonic.com/manufacture-guarantee-conditions>)

### Optical properties

- \_ Colour temperatures 2,700, 3,100, 3,500 and 4,100 K
- \_ Useful luminous flux 8.553 lm at Irated and tp = 25 °C
- \_ Efficacy of the LED module 172 lm/W at Irated and tp = 25 °C
- \_ High colour rendering index CRI > 80 and CRI > 90
- \_ Small colour tolerance (MacAdam 3)

### Mechanical properties


- \_ Module dimension LES09, LES13, LES15, LES17 and LES21
- \_ Housing with Snap-On feature for easy reflector mounting
- \_ 50 mm housing with 35 mm mounting hole distance acc. to Zhaga
- \_ Fixing holes for M3 screws

### System solution

- \_ Combine Tridonic's LED modules and dimmable drivers to achieve an outstanding system efficacy (configuration possible via <https://setbuilder.tridonic.com/>)

### Website

<http://www.tridonic.com/28002510>



Spotlights



Downlights



Linear



Area



Floor | Wall



Free-standing



Street




Decorative




High bay

**Module SLE G7 ADV**


Modules SLE advanced




Dimensions in mm, \*optical LES




Dimensions in mm, \*optical LES




Dimensions in mm, \*optical LES




Dimensions in mm, \*optical LES




Dimensions in mm, \*optical LES




Dimensions in mm, \*optical LES



Dimensions in mm, \*optical LES



Dimensions in mm, \*optical LES



Dimensions in mm, \*optical LES

## Ordering data

| Type                                                             | Article number | Colour temperature | Colour rendering index CRI | Packaging, carton | Weight per pc. |
|------------------------------------------------------------------|----------------|--------------------|----------------------------|-------------------|----------------|
| <b>SLE G7 09mm – Without housing</b>                             |                |                    |                            |                   |                |
| SLE G7 09mm 1200lm 830 R ADV                                     | 28002510       | 3,100 K            | >80                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 09mm 1200lm 840 R ADV                                     | 28002511       | 4,100 K            | >80                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 09mm 1200lm 927 R ADV                                     | 28002512       | 2,700 K            | >90                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 09mm 1200lm 930 R ADV                                     | 28002513       | 3,100 K            | >90                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 09mm 1200lm 940 R ADV                                     | 28002514       | 4,100 K            | >90                        | 20 pc(s).         | 0.001 kg       |
| <b>SLE G7 13mm – Without housing</b>                             |                |                    |                            |                   |                |
| SLE G7 13mm 3000lm 827 R ADV                                     | 28002515       | 2,700 K            | >80                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 13mm 3000lm 830 R ADV                                     | 28002516       | 3,100 K            | >80                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 13mm 3000lm 835 R ADV                                     | 28002517       | 3,500 K            | >80                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 13mm 3000lm 840 R ADV                                     | 28002518       | 4,100 K            | >80                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 13mm 3000lm 927 R ADV                                     | 28002519       | 2,700 K            | >90                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 13mm 3000lm 930 R ADV                                     | 28002520       | 3,100 K            | >90                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 13mm 3000lm 935 R ADV                                     | 28002521       | 3,500 K            | >90                        | 20 pc(s).         | 0.001 kg       |
| SLE G7 13mm 3000lm 940 R ADV                                     | 28002522       | 4,100 K            | >90                        | 20 pc(s).         | 0.001 kg       |
| <b>SLE G7 15mm – Without housing</b>                             |                |                    |                            |                   |                |
| SLE G7 15mm 4000lm 827 R ADV                                     | 28002523       | 2,700 K            | >80                        | 20 pc(s).         | 0.002 kg       |
| SLE G7 15mm 4000lm 830 R ADV                                     | 28002524       | 3,100 K            | >80                        | 20 pc(s).         | 0.002 kg       |
| SLE G7 15mm 4000lm 840 R ADV                                     | 28002526       | 4,100 K            | >80                        | 20 pc(s).         | 0.002 kg       |
| SLE G7 15mm 4000lm 927 R ADV                                     | 28002527       | 2,700 K            | >90                        | 20 pc(s).         | 0.002 kg       |
| SLE G7 15mm 4000lm 930 R ADV                                     | 28002528       | 3,100 K            | >90                        | 20 pc(s).         | 0.002 kg       |
| SLE G7 15mm 4000lm 940 R ADV                                     | 28002530       | 4,100 K            | >90                        | 20 pc(s).         | 0.002 kg       |
| <b>SLE G7 17mm – Without housing</b>                             |                |                    |                            |                   |                |
| SLE G7 17mm 5000lm 827 R ADV                                     | 28002588       | 2,700 K            | >80                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 17mm 5000lm 830 R ADV                                     | 28002589       | 3,100 K            | >80                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 17mm 5000lm 835 R ADV                                     | 28002590       | 3,500 K            | >80                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 17mm 5000lm 840 R ADV                                     | 28002591       | 4,100 K            | >80                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 17mm 5000lm 927 R ADV                                     | 28002592       | 2,700 K            | >90                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 17mm 5000lm 930 R ADV                                     | 28002593       | 3,100 K            | >90                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 17mm 5000lm 935 R ADV                                     | 28002594       | 3,500 K            | >90                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 17mm 5000lm 940 R ADV                                     | 28002595       | 4,100 K            | >90                        | 10 pc(s).         | 0.002 kg       |
| <b>SLE G7 21mm – Without housing</b>                             |                |                    |                            |                   |                |
| SLE G7 21mm 6000lm 827 R ADV                                     | 28002596       | 2,700 K            | >80                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 21mm 6000lm 830 R ADV                                     | 28002597       | 3,100 K            | >80                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 21mm 6000lm 840 R ADV                                     | 28002599       | 4,100 K            | >80                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 21mm 6000lm 927 R ADV                                     | 28002600       | 2,700 K            | >90                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 21mm 6000lm 930 R ADV                                     | 28002601       | 3,100 K            | >90                        | 10 pc(s).         | 0.002 kg       |
| SLE G7 21mm 6000lm 940 R ADV                                     | 28002603       | 4,100 K            | >90                        | 10 pc(s).         | 0.002 kg       |
| <b>SLE G7 13mm – With housing</b>                                |                |                    |                            |                   |                |
| SLE G7 13mm 3000lm 830 H ADV                                     | 28002559       | 3,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 13mm 3000lm 840 H ADV                                     | 28002560       | 4,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 13mm 3000lm 927 H ADV                                     | 28004044       | 2,700 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 13mm 3000lm 930 H ADV                                     | 28002561       | 3,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 13mm 3000lm 935 H ADV                                     | 28004045       | 3,500 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 13mm 3000lm 940 H ADV                                     | 28002562       | 4,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 15mm – With housing</b>                                |                |                    |                            |                   |                |
| SLE G7 15mm 4000lm 830 H ADV                                     | 28002567       | 3,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 15mm 4000lm 840 H ADV                                     | 28002568       | 4,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 15mm 4000lm 930 H ADV                                     | 28002569       | 3,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 15mm 4000lm 940 H ADV                                     | 28002570       | 4,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 17mm – With housing</b>                                |                |                    |                            |                   |                |
| SLE G7 17mm 5000lm 827 H ADV                                     | 28002612       | 2,700 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 17mm 5000lm 830 H ADV                                     | 28002613       | 3,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 17mm 5000lm 835 H ADV                                     | 28002614       | 3,500 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 17mm 5000lm 840 H ADV                                     | 28002615       | 4,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 17mm 5000lm 927 H ADV                                     | 28002616       | 2,700 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 17mm 5000lm 930 H ADV                                     | 28002617       | 3,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 17mm 5000lm 935 H ADV                                     | 28002618       | 3,500 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 17mm 5000lm 940 H ADV                                     | 28002619       | 4,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 21mm – With housing</b>                                |                |                    |                            |                   |                |
| SLE G7 21mm 6000lm 827 H ADV                                     | 28002631       | 2,700 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 21mm 6000lm 830 H ADV                                     | 28002632       | 3,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 21mm 6000lm 840 H ADV                                     | 28002633       | 4,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 21mm 6000lm 927 H ADV                                     | 28002634       | 2,700 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 21mm 6000lm 930 H ADV                                     | 28002635       | 3,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 21mm 6000lm 940 H ADV                                     | 28002637       | 4,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 15mm – With housing and thermal interface material</b> |                |                    |                            |                   |                |
| SLE G7 15mm 4000lm 830 H ADV T                                   | 28002670       | 3,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| SLE G7 15mm 4000lm 840 H ADV T                                   | 28002671       | 4,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |

| Type                                                             | Article number  | Colour temperature | Colour rendering index CRI | Packaging, carton | Weight per pc. |
|------------------------------------------------------------------|-----------------|--------------------|----------------------------|-------------------|----------------|
| <b>SLE G7 15mm 4000lm 930 H ADV T</b>                            | <b>28002672</b> | 3,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 15mm 4000lm 940 H ADV T</b>                            | <b>28002673</b> | 4,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 17mm – With housing and thermal interface material</b> |                 |                    |                            |                   |                |
| <b>SLE G7 17mm 5000lm 830 H ADV T</b>                            | <b>28002620</b> | 3,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 17mm 5000lm 840 H ADV T</b>                            | <b>28002621</b> | 4,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 17mm 5000lm 930 H ADV T</b>                            | <b>28002622</b> | 3,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 17mm 5000lm 935 H ADV T</b>                            | <b>28002623</b> | 3,500 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 17mm 5000lm 940 H ADV T</b>                            | <b>28002624</b> | 4,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 21mm – With housing and thermal interface material</b> |                 |                    |                            |                   |                |
| <b>SLE G7 21mm 6000lm 830 H ADV T</b>                            | <b>28002638</b> | 3,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 21mm 6000lm 840 H ADV T</b>                            | <b>28002639</b> | 4,100 K            | >80                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 21mm 6000lm 930 H ADV T</b>                            | <b>28002640</b> | 3,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |
| <b>SLE G7 21mm 6000lm 940 H ADV T</b>                            | <b>28002641</b> | 4,100 K            | >90                        | 50 pc(s).         | 0.007 kg       |

#### Technical data

|                                                                                   |                                                       |
|-----------------------------------------------------------------------------------|-------------------------------------------------------|
| Beam characteristic                                                               | 115°                                                  |
| Ambient temperature $t_a$                                                         | -30 ... +80 °C                                        |
| $t_p$ rated                                                                       | 65 °C                                                 |
| $t_c$ <sup>①</sup>                                                                | 105 °C                                                |
| I <sub>rated</sub> for LES09                                                      | 350 mA                                                |
| I <sub>rated</sub> for LES13                                                      | 500 mA                                                |
| I <sub>rated</sub> for LES15                                                      | 900 mA                                                |
| I <sub>rated</sub> for LES17                                                      | 1,050 mA                                              |
| I <sub>rated</sub> for LES21                                                      | 1,400 mA                                              |
| I <sub>max</sub> for LES09 <sup>①</sup>                                           | 550 mA                                                |
| I <sub>max</sub> for LES13 <sup>①</sup>                                           | 990 mA                                                |
| I <sub>max</sub> for LES15 <sup>①</sup>                                           | 1,320 mA                                              |
| I <sub>max</sub> for LES17 <sup>①</sup>                                           | 1,540 mA                                              |
| I <sub>max</sub> for LES21 <sup>①</sup>                                           | 2,200 mA                                              |
| Max. permissible LF current ripple for LES09                                      | 720 mA                                                |
| Max. permissible LF current ripple for LES13                                      | 1,440 mA                                              |
| Max. permissible LF current ripple for LES15                                      | 1,920 mA                                              |
| Max. permissible LF current ripple for LES17                                      | 1,680 mA                                              |
| Max. permissible LF current ripple for LES21                                      | 2,400 mA                                              |
| Max. permissible peak current for LES09                                           | 1,080 mA / max. 8 ms                                  |
| Max. permissible peak current for LES13                                           | 1,800 mA / max. 8 ms                                  |
| Max. permissible peak current for LES15                                           | 2,160 mA / max. 8 ms                                  |
| Max. permissible peak current for LES17                                           | 2,520 mA / max. 8 ms                                  |
| Max. permissible peak current for LES21                                           | 3,600 mA / max. 8 ms                                  |
| Max. working voltage for insulation SELV <sup>②</sup>                             | < 60 V                                                |
| Insulation test voltage                                                           | 0.5 kV                                                |
| CTI of the printed circuit board                                                  | ≥ 600                                                 |
| ESD classification                                                                | Severity level 4                                      |
| Risk group (IEC 62471) for LES09 (at I <sub>max</sub> )                           | RG2 (E <sub>thr</sub> = 1635 lx, RG1 at d ≥ 897 mm)   |
| Risk group (IEC 62471) for LES09 (at I ≤ 500 mA)                                  | RG1                                                   |
| Risk group (IEC 62471) for LES13 (at I <sub>max</sub> )                           | RG2 (E <sub>thr</sub> = 1635 lx, RG1 at d ≥ 1,220 mm) |
| Risk group (IEC 62471) for LES13 (at I ≤ 900 mA)                                  | RG1                                                   |
| Risk group (IEC 62471) for LES15 (at I <sub>max</sub> )                           | RG2 (E <sub>thr</sub> = 1635 lx, RG1 at d = 1,410 mm) |
| Risk group (IEC 62471) for LES15 (at I ≤ 1200 mA)                                 | RG1                                                   |
| Risk group (IEC 62471) for LES17 (at I <sub>max</sub> )                           | RG2 (E <sub>thr</sub> = 1771 lx, RG1 at d = 1,145 mm) |
| Risk group (IEC 62471) for LES17 (at I ≤ 1400 mA)                                 | RG1                                                   |
| Risk group (IEC 62471) for LES21                                                  | RG1                                                   |
| Type of protection                                                                | IP00                                                  |
| Lumen maintenance L70B50                                                          | 55,000 h                                              |
| Guarantee (conditions at <a href="http://www.tridonic.com">www.tridonic.com</a> ) | 5 Year(s)                                             |

#### Approval marks



#### Standards

EN 62031, EN 62471, EN 62717, IEC 61000-4-2, UL 8750

## Specific technical data

| Type                                                 | Article number | Photometric code | Useful luminous flux at $t_p = 25^\circ\text{C}$ | Expected luminous flux at $t_p$ rated | Typ. forward current | Min. forward voltage at $t_p$ rated | Max. forward voltage at $t_p = 25^\circ\text{C}$ | Power consumption $P_{\text{on}}$ at $t_p = 25^\circ\text{C}$ | Efficacy of the module at $t_p = 25^\circ\text{C}$ | Expected efficacy of the module at $t_p$ rated | Colour rendering index CRI |
|------------------------------------------------------|----------------|------------------|--------------------------------------------------|---------------------------------------|----------------------|-------------------------------------|--------------------------------------------------|---------------------------------------------------------------|----------------------------------------------------|------------------------------------------------|----------------------------|
| <b>SLE 09mm 1200lm – Operating mode HE at 250 mA</b> |                |                  |                                                  |                                       |                      |                                     |                                                  |                                                               |                                                    |                                                |                            |
| SLE G7 09mm 1200lm 830 R ADV                         | 28002510       | 830/359          | –                                                | 1,320 lm                              | 250 mA               | 31,5 V                              | 37,5 V                                           | –                                                             | –                                                  | 154 lm/W                                       | >80                        |
| SLE G7 09mm 1200lm 840 R ADV                         | 28002511       | 840/359          | –                                                | 1,385 lm                              | 250 mA               | 31,5 V                              | 37,5 V                                           | –                                                             | –                                                  | 161 lm/W                                       | >80                        |
| SLE G7 09mm 1200lm 927 R ADV                         | 28002512       | 927/359          | –                                                | 1,050 lm                              | 250 mA               | 31,5 V                              | 37,5 V                                           | –                                                             | –                                                  | 123 lm/W                                       | >90                        |
| SLE G7 09mm 1200lm 930 R ADV                         | 28002513       | 930/359          | –                                                | 1,118 lm                              | 250 mA               | 31,5 V                              | 37,5 V                                           | –                                                             | –                                                  | 131 lm/W                                       | >90                        |
| SLE G7 09mm 1200lm 940 R ADV                         | 28002514       | 940/359          | –                                                | 1,172 lm                              | 250 mA               | 31,5 V                              | 37,5 V                                           | –                                                             | –                                                  | 137 lm/W                                       | >90                        |
| <b>SLE 09mm 1200lm – Operating mode NM at 350 mA</b> |                |                  |                                                  |                                       |                      |                                     |                                                  |                                                               |                                                    |                                                |                            |
| SLE G7 09mm 1200lm 830 R ADV                         | 28002510       | 830/359          | 1,926 lm                                         | 1,779 lm                              | 350 mA               | 32,4 V                              | 38,6 V                                           | 12,5 W                                                        | 154 lm/W                                           | 144 lm/W                                       | >80                        |
| SLE G7 09mm 1200lm 840 R ADV                         | 28002511       | 840/359          | 2,014 lm                                         | 1,869 lm                              | 350 mA               | 32,4 V                              | 38,6 V                                           | 12,5 W                                                        | 161 lm/W                                           | 151 lm/W                                       | >80                        |
| SLE G7 09mm 1200lm 927 R ADV                         | 28002512       | 927/359          | 1,512 lm                                         | 1,406 lm                              | 350 mA               | 32,4 V                              | 38,6 V                                           | 12,5 W                                                        | 121 lm/W                                           | 113 lm/W                                       | >90                        |
| SLE G7 09mm 1200lm 930 R ADV                         | 28002513       | 930/359          | 1,627 lm                                         | 1,507 lm                              | 350 mA               | 32,4 V                              | 38,6 V                                           | 12,5 W                                                        | 130 lm/W                                           | 122 lm/W                                       | >90                        |
| SLE G7 09mm 1200lm 940 R ADV                         | 28002514       | 940/359          | 1,699 lm                                         | 1,572 lm                              | 350 mA               | 32,4 V                              | 38,6 V                                           | 12,5 W                                                        | 136 lm/W                                           | 128 lm/W                                       | >90                        |
| <b>SLE 09mm 1200lm – Operating mode HO at 500 mA</b> |                |                  |                                                  |                                       |                      |                                     |                                                  |                                                               |                                                    |                                                |                            |
| SLE G7 09mm 1200lm 830 R ADV                         | 28002510       | 830/359          | –                                                | 2,425 lm                              | 500 mA               | 32,8 V                              | 39,0 V                                           | –                                                             | –                                                  | 136 lm/W                                       | >80                        |
| SLE G7 09mm 1200lm 840 R ADV                         | 28002511       | 840/359          | –                                                | 2,537 lm                              | 500 mA               | 32,8 V                              | 39,0 V                                           | –                                                             | –                                                  | 142 lm/W                                       | >80                        |
| SLE G7 09mm 1200lm 927 R ADV                         | 28002512       | 927/359          | –                                                | 1,907 lm                              | 500 mA               | 32,8 V                              | 39,0 V                                           | –                                                             | –                                                  | 107 lm/W                                       | >90                        |
| SLE G7 09mm 1200lm 930 R ADV                         | 28002513       | 930/359          | –                                                | 2,046 lm                              | 500 mA               | 32,8 V                              | 39,0 V                                           | –                                                             | –                                                  | 115 lm/W                                       | >90                        |
| SLE G7 09mm 1200lm 940 R ADV                         | 28002514       | 940/359          | –                                                | 2,138 lm                              | 500 mA               | 32,8 V                              | 39,0 V                                           | –                                                             | –                                                  | 120 lm/W                                       | >90                        |
| <b>SLE 13mm 3000lm – Operating mode HE at 350 mA</b> |                |                  |                                                  |                                       |                      |                                     |                                                  |                                                               |                                                    |                                                |                            |
| SLE G7 13mm 3000lm 827 R ADV                         | 28002515       | 827/359          | –                                                | 1,793 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 152 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 830 R ADV                         | 28002516       | 830/359          | –                                                | 1,897 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 161 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 835 R ADV                         | 28002517       | 835/359          | –                                                | 1,976 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 167 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 840 R ADV                         | 28002518       | 840/359          | –                                                | 2,008 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 170 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 927 R ADV                         | 28002519       | 927/359          | –                                                | 1,545 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 131 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 930 R ADV                         | 28002520       | 930/359          | –                                                | 1,627 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 137 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 935 R ADV                         | 28002521       | 935/359          | –                                                | 1,591 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 135 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 940 R ADV                         | 28002522       | 940/359          | –                                                | 1,672 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 142 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 830 H ADV                         | 28002559       | 830/359          | –                                                | 1,595 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 135 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 840 H ADV                         | 28002560       | 840/359          | –                                                | 1,688 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 143 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 927 H ADV                         | 28004044       | 927/359          | –                                                | 1,298 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 110 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 930 H ADV                         | 28002561       | 930/359          | –                                                | 1,368 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 115 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 935 H ADV                         | 28004045       | 935/359          | –                                                | 1,337 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 113 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 940 H ADV                         | 28002562       | 940/359          | –                                                | 1,405 lm                              | 350 mA               | 30,9 V                              | 36,8 V                                           | –                                                             | –                                                  | 119 lm/W                                       | >90                        |
| <b>SLE 13mm 3000lm – Operating mode NM at 500 mA</b> |                |                  |                                                  |                                       |                      |                                     |                                                  |                                                               |                                                    |                                                |                            |
| SLE G7 13mm 3000lm 827 R ADV                         | 28002515       | 827/359          | 2,680 lm                                         | 2,491 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 152 lm/W                                           | 143 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 830 R ADV                         | 28002516       | 830/359          | 2,827 lm                                         | 2,626 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 161 lm/W                                           | 151 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 835 R ADV                         | 28002517       | 835/359          | 2,930 lm                                         | 2,724 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 166 lm/W                                           | 157 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 840 R ADV                         | 28002518       | 840/359          | 2,988 lm                                         | 2,772 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 170 lm/W                                           | 160 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 927 R ADV                         | 28002519       | 927/359          | 2,307 lm                                         | 2,139 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 131 lm/W                                           | 123 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 930 R ADV                         | 28002520       | 930/359          | 2,416 lm                                         | 2,246 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 137 lm/W                                           | 129 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 935 R ADV                         | 28002521       | 935/359          | 2,368 lm                                         | 2,200 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 135 lm/W                                           | 127 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 940 R ADV                         | 28002522       | 940/359          | 2,494 lm                                         | 2,315 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 142 lm/W                                           | 133 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 830 H ADV                         | 28002559       | 830/359          | 2,376 lm                                         | 2,207 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 135 lm/W                                           | 127 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 840 H ADV                         | 28002560       | 840/359          | 2,511 lm                                         | 2,330 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 143 lm/W                                           | 134 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 927 H ADV                         | 28004044       | 927/359          | 1,939 lm                                         | 1,797 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 110 lm/W                                           | 104 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 930 H ADV                         | 28002561       | 930/359          | 2,030 lm                                         | 1,888 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 115 lm/W                                           | 109 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 935 H ADV                         | 28004045       | 935/359          | 1,990 lm                                         | 1,848 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 113 lm/W                                           | 107 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 940 H ADV                         | 28002562       | 940/359          | 2,096 lm                                         | 1,888 lm                              | 500 mA               | 31,8 V                              | 37,9 V                                           | 17,6 W                                                        | 119 lm/W                                           | 112 lm/W                                       | >90                        |
| <b>SLE 13mm 3000lm – Operating mode HO at 900 mA</b> |                |                  |                                                  |                                       |                      |                                     |                                                  |                                                               |                                                    |                                                |                            |
| SLE G7 13mm 3000lm 827 R ADV                         | 28002515       | 827/359          | –                                                | 4,152 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 124 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 830 R ADV                         | 28002516       | 830/359          | –                                                | 4,379 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 131 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 835 R ADV                         | 28002517       | 835/359          | –                                                | 4,513 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 135 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 840 R ADV                         | 28002518       | 840/359          | –                                                | 4,595 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 138 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 927 R ADV                         | 28002519       | 927/359          | –                                                | 3,564 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 106 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 930 R ADV                         | 28002520       | 930/359          | –                                                | 3,744 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 111 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 935 R ADV                         | 28002521       | 935/359          | –                                                | 3,660 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 109 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 940 R ADV                         | 28002522       | 840/359          | –                                                | 3,779 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 115 lm/W                                       | >90                        |
| SLE G7 13mm 3000lm 830 H ADV                         | 28002559       | 830/359          | –                                                | 3,680 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 110 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 840 H ADV                         | 28002560       | 840/359          | –                                                | 3,861 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 116 lm/W                                       | >80                        |
| SLE G7 13mm 3000lm 927 H ADV                         | 28004044       | 927/359          | –                                                | 2,996 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 90 lm/W                                        | >90                        |
| SLE G7 13mm 3000lm 930 H ADV                         | 28002561       | 930/359          | –                                                | 3,146 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 94 lm/W                                        | >90                        |
| SLE G7 13mm 3000lm 935 H ADV                         | 28004045       | 935/359          | –                                                | 3,076 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 92 lm/W                                        | >90                        |
| SLE G7 13mm 3000lm 940 H ADV                         | 28002562       | 940/359          | –                                                | 3,176 lm                              | 900 mA               | 34,0 V                              | 40,5 V                                           | –                                                             | –                                                  | 97 lm/W                                        | >90                        |
| <b>SLE 15mm 4000lm – Operating mode HE at 500 mA</b> |                |                  |                                                  |                                       |                      |                                     |                                                  |                                                               |                                                    |                                                |                            |
| SLE G7 15mm 4000lm 827 R ADV                         | 28002523       | 827/359          | –                                                | 2,616 lm                              | 500 mA               | 30,7 V                              | 36,6 V                                           | –                                                             | –                                                  | 157 lm/W                                       | >80                        |
| SLE G7 15mm 4000lm 830 R ADV                         | 28002524       | 830/359          | –                                                | 2,672 lm                              | 500 mA               | 30,7 V                              | 36,6 V                                           | –                                                             | –                                                  | 159 lm/W                                       | >80                        |
| SLE G7 15mm 4000lm 840 R ADV                         | 28002526       | 840/359          | –                                                | 2,404 lm                              | 500 mA               | 30,7 V                              | 36,6 V                                           | –                                                             | –                                                  | 171 lm/W                                       | >80                        |
| SLE G7 15mm 4000lm 927 R ADV                         | 28002527       | 927/359          | –                                                | 2,107 lm                              | 500 mA               | 30,7 V                              | 36,6 V                                           | –                                                             | –                                                  | 126 lm/W                                       | >90                        |



| Type                                                   | Article number | Photometric code | Useful luminous flux at tp = 25 °C | Expected luminous flux at tp rated | Typ. forward current | Min. forward voltage at tp rated | Max. forward voltage at tp = 25 °C | Power consumption Pon at tp = 25 °C | Efficacy of the module at tp = 25 °C | Expected efficacy of the module at tp rated | Colour rendering index CRI |
|--------------------------------------------------------|----------------|------------------|------------------------------------|------------------------------------|----------------------|----------------------------------|------------------------------------|-------------------------------------|--------------------------------------|---------------------------------------------|----------------------------|
| SLE G7 15mm 4000lm 930 R ADV                           | 28002528       | 930/359          | –                                  | 2,251 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 135 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 940 R ADV                           | 28002530       | 940/359          | –                                  | 1,968 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 140 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 830 H ADV                           | 28002567       | 830/359          | –                                  | 2,246 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 134 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 840 H ADV                           | 28002568       | 840/359          | –                                  | 2,404 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 144 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 930 H ADV                           | 28002569       | 930/359          | –                                  | 1,892 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 114 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 940 H ADV                           | 28002570       | 940/359          | –                                  | 1,968 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 118 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 830 H ADV T                         | 28002670       | 830/359          | –                                  | 2,246 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 134 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 840 H ADV T                         | 28002671       | 840/359          | –                                  | 2,404 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 144 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 930 H ADV T                         | 28002672       | 930/359          | –                                  | 1,892 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 114 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 940 H ADV T                         | 28002673       | 940/359          | –                                  | 1,968 lm                           | 500 mA               | 30.7 V                           | 36.6 V                             | –                                   | –                                    | 118 lm/W                                    | >90                        |
| <b>SLE 15mm 4000lm – Operating mode NM at 900 mA</b>   |                |                  |                                    |                                    |                      |                                  |                                    |                                     |                                      |                                             |                            |
| SLE G7 15mm 4000lm 827 R ADV                           | 28002523       | 827/359          | 4,808 lm                           | 4,453 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 150 lm/W                             | 141 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 830 R ADV                           | 28002524       | 830/359          | 4,918 lm                           | 4,550 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 154 lm/W                             | 144 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 840 R ADV                           | 28002526       | 840/359          | 5,222 lm                           | 4,832 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 163 lm/W                             | 153 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 927 R ADV                           | 28002527       | 927/359          | 3,874 lm                           | 3,583 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 121 lm/W                             | 113 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 930 R ADV                           | 28002528       | 930/359          | 4,132 lm                           | 3,822 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 129 lm/W                             | 121 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 940 R ADV                           | 28002530       | 940/359          | 4,312 lm                           | 3,998 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 135 lm/W                             | 126 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 830 H ADV                           | 28002567       | 830/359          | 4,133 lm                           | 3,824 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 129 lm/W                             | 121 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 840 H ADV                           | 28002568       | 840/359          | 4,389 lm                           | 4,061 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 137 lm/W                             | 129 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 930 H ADV                           | 28002569       | 930/359          | 3,473 lm                           | 3,212 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 109 lm/W                             | 102 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 940 H ADV                           | 28002570       | 940/359          | 3,624 lm                           | 3,360 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 113 lm/W                             | 106 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 830 H ADV T                         | 28002670       | 830/359          | 4,133 lm                           | 3,824 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 129 lm/W                             | 121 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 840 H ADV T                         | 28002671       | 840/359          | 4,389 lm                           | 4,061 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 137 lm/W                             | 129 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 930 H ADV T                         | 28002672       | 930/359          | 3,473 lm                           | 3,212 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 109 lm/W                             | 102 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 940 H ADV T                         | 28002673       | 940/359          | 3,624 lm                           | 3,360 lm                           | 900 mA               | 32.2 V                           | 38.3 V                             | 32.0 W                              | 113 lm/W                             | 106 lm/W                                    | >90                        |
| <b>SLE 15mm 4000lm – Operating mode HO at 1,200 mA</b> |                |                  |                                    |                                    |                      |                                  |                                    |                                     |                                      |                                             |                            |
| SLE G7 15mm 4000lm 827 R ADV                           | 28002523       | 827/359          | –                                  | 5,716 lm                           | 1,200 mA             | 33.2 V                           | 39.5 V                             | –                                   | –                                    | 132 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 830 R ADV                           | 28002524       | 830/359          | –                                  | 5,838 lm                           | 1,200 mA             | 33.2 V                           | 39.5 V                             | –                                   | –                                    | 134 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 840 R ADV                           | 28002526       | 840/359          | –                                  | 6,182 lm                           | 1,200 mA             | 33.2 V                           | 39.5 V                             | –                                   | –                                    | 143 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 927 R ADV                           | 28002527       | 927/359          | –                                  | 4,592 lm                           | 1,200 mA             | 33.2 V                           | 39.5 V                             | –                                   | –                                    | 106 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 930 R ADV                           | 28002528       | 930/359          | –                                  | 4,902 lm                           | 1,200 mA             | 33.2 V                           | 39.5 V                             | –                                   | –                                    | 113 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 940 R ADV                           | 28002530       | 940/359          | –                                  | 5,131 lm                           | 1,200 mA             | 33.2 V                           | 39.5 V                             | –                                   | –                                    | 118 lm/W                                    | >90                        |
| SLE G7 15mm 4000lm 830 H ADV                           | 28002567       | 830/359          | –                                  | 4,906 lm                           | 1,200 mA             | 32.2 V                           | 39.5 V                             | –                                   | –                                    | 113 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 840 H ADV                           | 28002568       | 840/359          | –                                  | 5,196 lm                           | 1,200 mA             | 32.2 V                           | 39.5 V                             | –                                   | –                                    | 120 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 930 H ADV                           | 28002569       | 930/359          | –                                  | 4,120 lm                           | 1,200 mA             | 32.2 V                           | 39.5 V                             | –                                   | –                                    | 95 lm/W                                     | >90                        |
| SLE G7 15mm 4000lm 940 H ADV                           | 28002570       | 940/359          | –                                  | 4,312 lm                           | 1,200 mA             | 32.2 V                           | 39.5 V                             | –                                   | –                                    | 99 lm/W                                     | >90                        |
| SLE G7 15mm 4000lm 830 H ADV T                         | 28002670       | 830/359          | –                                  | 4,906 lm                           | 1,200 mA             | 32.2 V                           | 39.5 V                             | –                                   | –                                    | 113 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 840 H ADV T                         | 28002671       | 840/359          | –                                  | 5,196 lm                           | 1,200 mA             | 32.2 V                           | 39.5 V                             | –                                   | –                                    | 120 lm/W                                    | >80                        |
| SLE G7 15mm 4000lm 930 H ADV T                         | 28002672       | 930/359          | –                                  | 4,120 lm                           | 1,200 mA             | 32.2 V                           | 39.5 V                             | –                                   | –                                    | 95 lm/W                                     | >90                        |
| SLE G7 15mm 4000lm 940 H ADV T                         | 28002673       | 940/359          | –                                  | 4,312 lm                           | 1,200 mA             | 32.2 V                           | 39.5 V                             | –                                   | –                                    | 99 lm/W                                     | >90                        |
| <b>SLE 17mm 5000lm – Operating mode HE at 500 mA</b>   |                |                  |                                    |                                    |                      |                                  |                                    |                                     |                                      |                                             |                            |
| SLE G7 17mm 5000lm 827 R ADV                           | 28002588       | 827/359          | –                                  | 2,615 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 153 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 830 R ADV                           | 28002589       | 830/359          | –                                  | 2,816 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 168 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 835 R ADV                           | 28002590       | 835/359          | –                                  | 2,829 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 170 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 840 R ADV                           | 28002591       | 840/359          | –                                  | 2,971 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 178 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 927 R ADV                           | 28002592       | 927/359          | –                                  | 2,225 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 134 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 930 R ADV                           | 28002593       | 930/359          | –                                  | 2,449 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 147 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 935 R ADV                           | 28002594       | 935/359          | –                                  | 2,474 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 149 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 940 R ADV                           | 28002595       | 940/359          | –                                  | 2,536 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 152 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 827 H ADV                           | 28002612       | 827/359          | –                                  | 2,197 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 129 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 830 H ADV                           | 28002613       | 830/359          | –                                  | 2,367 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 142 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 835 H ADV                           | 28002614       | 835/359          | –                                  | 2,377 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 143 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 840 H ADV                           | 28002615       | 840/359          | –                                  | 2,497 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 150 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 927 H ADV                           | 28002616       | 927/359          | –                                  | 1,870 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 112 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 930 H ADV                           | 28002617       | 930/359          | –                                  | 2,058 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 123 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 935 H ADV                           | 28002618       | 935/359          | –                                  | 2,079 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 125 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 940 H ADV                           | 28002619       | 940/359          | –                                  | 2,131 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 128 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 830 H ADV T                         | 28002620       | 830/359          | –                                  | 2,367 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 142 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 840 H ADV T                         | 28002621       | 840/359          | –                                  | 2,497 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 150 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 930 H ADV T                         | 28002622       | 930/359          | –                                  | 2,058 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 123 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 935 H ADV T                         | 28002623       | 935/359          | –                                  | 2,079 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 125 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 940 H ADV T                         | 28002624       | 940/359          | –                                  | 2,131 lm                           | 500 mA               | 30.6 V                           | 36.7 V                             | –                                   | –                                    | 128 lm/W                                    | >90                        |
| <b>SLE 17mm 5000lm – Operating mode NM at 1,050 mA</b> |                |                  |                                    |                                    |                      |                                  |                                    |                                     |                                      |                                             |                            |
| SLE G7 17mm 5000lm 827 R ADV                           | 28002588       | 827/359          | 5,541 lm                           | 5,154 lm                           | 1,050 mA             | 32.0 V                           | 38.3 V                             | 37.3 W                              | 149 lm/W                             | 144 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 830 R ADV                           | 28002589       | 830/359          | 5,954 lm                           | 5,545 lm                           | 1,050 mA             | 32.0 V                           | 38.3 V                             | 37.3 W                              | 160 lm/W                             | 152 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 835 R ADV                           | 28002590       | 835/359          | 5,984 lm                           | 5,572 lm                           | 1,050 mA             | 32.0 V                           | 38.3 V                             | 37.3 W                              | 160 lm/W                             | 153 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 840 R ADV                           | 28002591       | 840/359          | 6,288 lm                           | 5,854 lm                           | 1,050 mA             | 32.0 V                           | 38.3 V                             | 37.3 W                              | 169 lm/W                             | 160 lm/W                                    | >80                        |
| SLE G7 17mm 5000lm 927 R ADV                           | 28002592       | 927/359          | 4,702 lm                           | 4,373 lm                           | 1,050 mA             | 32.0 V                           | 38.3 V                             | 37.3 W                              | 126 lm/W                             | 120 lm/W                                    | >90                        |
| SLE G7 17mm 5000lm 930 R ADV                           | 28002593       | 930/359          | 5,178 lm                           | 4,818 lm                           | 1,050 mA             | 32.0 V                           | 38.3 V                             | 37.3 W                              | 139 lm/W                             | 132 lm/W                                    | >90                        |



| Type                                                   | Article number | Photometric code | Useful luminous flux at $T_p = 25\text{ °C}$ | Expected luminous flux at $T_p$ rated | Typ. forward current | Min. forward voltage at $T_p$ rated | Max. forward voltage at $T_p = 25\text{ °C}$ | Power consumption $P_{on}$ at $T_p = 25\text{ °C}$ | Efficacy of the module at $T_p = 25\text{ °C}$ | Expected efficacy of the module at $T_p$ rated | Colour rendering index CRI |
|--------------------------------------------------------|----------------|------------------|----------------------------------------------|---------------------------------------|----------------------|-------------------------------------|----------------------------------------------|----------------------------------------------------|------------------------------------------------|------------------------------------------------|----------------------------|
| SLE G7 17mm 5000lm 935 R ADV                           | 28002594       | 935/359          | 5,248 lm                                     | 4,879 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 141 lm/W                                       | 134 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 940 R ADV                           | 28002595       | 940/359          | 5,368 lm                                     | 4,993 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 144 lm/W                                       | 137 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 827 H ADV                           | 28002612       | 827/359          | 4,657 lm                                     | 4,331 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 125 lm/W                                       | 121 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 830 H ADV                           | 28002613       | 830/359          | 5,004 lm                                     | 4,660 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 134 lm/W                                       | 128 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 835 H ADV                           | 28002614       | 835/359          | 5,029 lm                                     | 4,682 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 135 lm/W                                       | 128 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 840 H ADV                           | 28002615       | 840/359          | 5,284 lm                                     | 4,919 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 142 lm/W                                       | 134 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 927 H ADV                           | 28002616       | 927/359          | 3,952 lm                                     | 3,675 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 106 lm/W                                       | 101 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 930 H ADV                           | 28002617       | 930/359          | 4,352 lm                                     | 4,049 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 117 lm/W                                       | 111 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 935 H ADV                           | 28002618       | 935/359          | 4,410 lm                                     | 4,100 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 118 lm/W                                       | 112 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 940 H ADV                           | 28002619       | 940/359          | 4,511 lm                                     | 4,196 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 121 lm/W                                       | 115 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 830 H ADV T                         | 28002620       | 830/359          | 5,004 lm                                     | 4,660 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 134 lm/W                                       | 128 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 840 H ADV T                         | 28002621       | 840/359          | 5,284 lm                                     | 4,919 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 142 lm/W                                       | 134 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 930 H ADV T                         | 28002622       | 930/359          | 4,352 lm                                     | 4,049 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 117 lm/W                                       | 111 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 935 H ADV T                         | 28002623       | 935/359          | 4,410 lm                                     | 4,100 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 118 lm/W                                       | 112 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 940 H ADV T                         | 28002624       | 940/359          | 4,511 lm                                     | 4,196 lm                              | 1,050 mA             | 32.0 V                              | 38.3 V                                       | 37.3 W                                             | 121 lm/W                                       | 115 lm/W                                       | >90                        |
| <b>SLE 17mm 5000lm – Operating mode HO at 1,400 mA</b> |                |                  |                                              |                                       |                      |                                     |                                              |                                                    |                                                |                                                |                            |
| SLE G7 17mm 5000lm 827 R ADV                           | 28002588       | 827/359          | –                                            | 6,636 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 125 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 830 R ADV                           | 28002589       | 830/359          | –                                            | 7,133 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 143 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 835 R ADV                           | 28002590       | 835/359          | –                                            | 7,173 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 144 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 840 R ADV                           | 28002591       | 840/359          | –                                            | 7,532 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 151 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 927 R ADV                           | 28002592       | 927/359          | –                                            | 5,631 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 113 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 930 R ADV                           | 28002593       | 930/359          | –                                            | 6,198 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 125 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 935 R ADV                           | 28002594       | 935/359          | –                                            | 6,286 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 126 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 940 R ADV                           | 28002595       | 940/359          | –                                            | 6,434 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 129 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 827 H ADV                           | 28002612       | 827/359          | –                                            | 5,577 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 105 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 830 H ADV                           | 28002613       | 830/359          | –                                            | 5,995 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 120 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 835 H ADV                           | 28002614       | 835/359          | –                                            | 6,028 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 121 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 840 H ADV                           | 28002615       | 840/359          | –                                            | 6,330 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 127 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 927 H ADV                           | 28002616       | 927/359          | –                                            | 4,732 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 95 lm/W                                        | >90                        |
| SLE G7 17mm 5000lm 930 H ADV                           | 28002617       | 930/359          | –                                            | 5,208 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 108 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 935 H ADV                           | 28002618       | 935/359          | –                                            | 5,282 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 106 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 940 H ADV                           | 28002619       | 940/359          | –                                            | 5,407 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 109 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 830 H ADV T                         | 28002620       | 830/359          | –                                            | 5,995 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 120 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 840 H ADV T                         | 28002621       | 840/359          | –                                            | 6,330 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 127 lm/W                                       | >80                        |
| SLE G7 17mm 5000lm 930 H ADV T                         | 28002622       | 930/359          | –                                            | 5,208 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 105 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 935 H ADV T                         | 28002623       | 935/359          | –                                            | 5,282 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 106 lm/W                                       | >90                        |
| SLE G7 17mm 5000lm 940 H ADV T                         | 28002624       | 940/359          | –                                            | 5,407 lm                              | 1,400 mA             | 32.7 V                              | 39.2 V                                       | –                                                  | –                                              | 109 lm/W                                       | >90                        |
| <b>SLE 21mm 6000lm – Operating mode HE at 700 mA</b>   |                |                  |                                              |                                       |                      |                                     |                                              |                                                    |                                                |                                                |                            |
| SLE G7 21mm 6000lm 827 R ADV                           | 28002596       | 827/359          | –                                            | 3,756 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 160 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 830 R ADV                           | 28002597       | 830/359          | –                                            | 4,002 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 172 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 840 R ADV                           | 28002599       | 840/359          | –                                            | 4,207 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 180 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 927 R ADV                           | 28002600       | 927/359          | –                                            | 3,125 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 134 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 930 R ADV                           | 28002601       | 930/359          | –                                            | 3,441 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 147 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 940 R ADV                           | 28002603       | 940/359          | –                                            | 3,596 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 154 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 827 H ADV                           | 28002631       | 827/359          | –                                            | 3,156 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 135 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 830 H ADV                           | 28002632       | 830/359          | –                                            | 3,363 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 144 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 840 H ADV                           | 28002633       | 840/359          | –                                            | 3,536 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 152 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 927 H ADV                           | 28002634       | 927/359          | –                                            | 2,627 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 113 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 930 H ADV                           | 28002635       | 930/359          | –                                            | 2,892 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 123 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 940 H ADV                           | 28002637       | 940/359          | –                                            | 3,022 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 130 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 830 H ADV T                         | 28002638       | 830/359          | –                                            | 3,363 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 144 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 840 H ADV T                         | 28002639       | 840/359          | –                                            | 3,536 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 152 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 930 H ADV T                         | 28002640       | 930/359          | –                                            | 2,892 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 123 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 940 H ADV T                         | 28002641       | 940/359          | –                                            | 3,022 lm                              | 700 mA               | 30.6 V                              | 36.7 V                                       | –                                                  | –                                              | 130 lm/W                                       | >90                        |
| <b>SLE 21mm 6000lm – Operating mode NM at 1,400 mA</b> |                |                  |                                              |                                       |                      |                                     |                                              |                                                    |                                                |                                                |                            |
| SLE G7 21mm 6000lm 827 R ADV                           | 28002596       | 827/359          | 7,626 lm                                     | 7,089 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 154 lm/W                                       | 145 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 830 R ADV                           | 28002597       | 830/359          | 8,132 lm                                     | 7,563 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 164 lm/W                                       | 156 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 840 R ADV                           | 28002599       | 840/359          | 8,553 lm                                     | 7,959 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 172 lm/W                                       | 164 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 927 R ADV                           | 28002600       | 927/359          | 6,357 lm                                     | 5,913 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 128 lm/W                                       | 121 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 930 R ADV                           | 28002601       | 930/359          | 6,981 lm                                     | 6,494 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 141 lm/W                                       | 133 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 940 R ADV                           | 28002603       | 940/359          | 7,311 lm                                     | 6,796 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 147 lm/W                                       | 139 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 827 H ADV                           | 28002631       | 827/359          | 6,409 lm                                     | 5,958 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 129 lm/W                                       | 122 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 830 H ADV                           | 28002632       | 830/359          | 6,834 lm                                     | 6,356 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 138 lm/W                                       | 131 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 840 H ADV                           | 28002633       | 840/359          | 7,188 lm                                     | 6,689 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 145 lm/W                                       | 137 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 927 H ADV                           | 28002634       | 927/359          | 5,342 lm                                     | 4,970 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 108 lm/W                                       | 102 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 930 H ADV                           | 28002635       | 930/359          | 5,867 lm                                     | 5,457 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 118 lm/W                                       | 112 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 940 H ADV                           | 28002637       | 940/359          | 6,144 lm                                     | 5,711 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 124 lm/W                                       | 117 lm/W                                       | >90                        |
| SLE G7 21mm 6000lm 830 H ADV T                         | 28002638       | 830/359          | 6,834 lm                                     | 6,356 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 138 lm/W                                       | 131 lm/W                                       | >80                        |
| SLE G7 21mm 6000lm 840 H ADV T                         | 28002639       | 840/359          | 7,188 lm                                     | 6,689 lm                              | 1,400 mA             | 31.9 V                              | 38.2 V                                       | 49.6 W                                             | 145 lm/W                                       | 137 lm/W                                       | >80                        |

| Type                                                   | Article number  | Photometric code | Useful luminous flux at $t_p = 25^\circ\text{C}$ <sup>③</sup> | Expected luminous flux at $t_p$ rated <sup>④</sup> | Typ. forward current | Min. forward voltage at $t_p$ rated | Max. forward voltage at $t_p = 25^\circ\text{C}$ | Power consumption $P_{on}$ at $t_p = 25^\circ\text{C}$ <sup>⑤</sup> | Efficacy of the module at $t_p = 25^\circ\text{C}$ | Expected efficacy of the module at $t_p$ rated | Colour rendering index CRI |
|--------------------------------------------------------|-----------------|------------------|---------------------------------------------------------------|----------------------------------------------------|----------------------|-------------------------------------|--------------------------------------------------|---------------------------------------------------------------------|----------------------------------------------------|------------------------------------------------|----------------------------|
| <b>SLE G7 21mm 6000lm 930 H ADV T</b>                  | <b>28002640</b> | 930/359          | 5,867 lm                                                      | 5,457 lm                                           | 1,400 mA             | 31.9 V                              | 38.2 V                                           | 49.6 W                                                              | 118 lm/W                                           | 112 lm/W                                       | >90                        |
| <b>SLE G7 21mm 6000lm 940 H ADV T</b>                  | <b>28002641</b> | 940/359          | 6,144 lm                                                      | 5,711 lm                                           | 1,400 mA             | 31.9 V                              | 38.2 V                                           | 49.6 W                                                              | 124 lm/W                                           | 117 lm/W                                       | >90                        |
| <b>SLE 21mm 6000lm – Operating mode HO at 2,000 mA</b> |                 |                  |                                                               |                                                    |                      |                                     |                                                  |                                                                     |                                                    |                                                |                            |
| <b>SLE G7 21mm 6000lm 827 R ADV</b>                    | <b>28002596</b> | 827/359          | –                                                             | 9,695 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 136 lm/W                                       | >80                        |
| <b>SLE G7 21mm 6000lm 830 R ADV</b>                    | <b>28002597</b> | 830/359          | –                                                             | 10,339 lm                                          | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 145 lm/W                                       | >80                        |
| <b>SLE G7 21mm 6000lm 840 R ADV</b>                    | <b>28002599</b> | 840/359          | –                                                             | 10,879 lm                                          | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 153 lm/W                                       | >80                        |
| <b>SLE G7 21mm 6000lm 927 R ADV</b>                    | <b>28002600</b> | 927/359          | –                                                             | 8,084 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 113 lm/W                                       | >90                        |
| <b>SLE G7 21mm 6000lm 930 R ADV</b>                    | <b>28002601</b> | 930/359          | –                                                             | 8,880 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 124 lm/W                                       | >90                        |
| <b>SLE G7 21mm 6000lm 940 R ADV</b>                    | <b>28002603</b> | 940/359          | –                                                             | 9,292 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 130 lm/W                                       | >90                        |
| <b>SLE G7 21mm 6000lm 827 H ADV</b>                    | <b>28002631</b> | 827/359          | –                                                             | 8,148 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 114 lm/W                                       | >80                        |
| <b>SLE G7 21mm 6000lm 830 H ADV</b>                    | <b>28002632</b> | 830/359          | –                                                             | 8,689 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 122 lm/W                                       | >80                        |
| <b>SLE G7 21mm 6000lm 840 H ADV</b>                    | <b>28002633</b> | 840/359          | –                                                             | 9,143 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 128 lm/W                                       | >80                        |
| <b>SLE G7 21mm 6000lm 927 H ADV</b>                    | <b>28002634</b> | 927/359          | –                                                             | 6,794 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 95 lm/W                                        | >90                        |
| <b>SLE G7 21mm 6000lm 930 H ADV</b>                    | <b>28002635</b> | 930/359          | –                                                             | 7,463 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 104 lm/W                                       | >90                        |
| <b>SLE G7 21mm 6000lm 940 H ADV</b>                    | <b>28002637</b> | 940/359          | –                                                             | 7,809 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 109 lm/W                                       | >90                        |
| <b>SLE G7 21mm 6000lm 830 H ADV T</b>                  | <b>28002638</b> | 830/359          | –                                                             | 8,689 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 122 lm/W                                       | >80                        |
| <b>SLE G7 21mm 6000lm 840 H ADV T</b>                  | <b>28002639</b> | 840/359          | –                                                             | 9,143 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 128 lm/W                                       | >80                        |
| <b>SLE G7 21mm 6000lm 930 H ADV T</b>                  | <b>28002640</b> | 930/359          | –                                                             | 7,463 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 104 lm/W                                       | >90                        |
| <b>SLE G7 21mm 6000lm 940 H ADV T</b>                  | <b>28002641</b> | 940/359          | –                                                             | 7,809 lm                                           | 2,000 mA             | 32.8 V                              | 39.3 V                                           | –                                                                   | –                                                  | 109 lm/W                                       | >90                        |

① See derating curves in data sheet section 2.3.

② The detailed explanation, see data sheet section 3.1.


③ Tolerance of useful light flux - 0 % / + 15 %. Measurement uncertainty  $\pm 10$  %.

④ Tolerance of expected light flux - 0 % / + 15 %. Measurement uncertainty  $\pm 10$  %. Based on calculation.

⑤ Tolerance of power consumption  $P_{on}$   $\pm 10$  %. Measurement uncertainty  $\pm 5$  %.

Housing for SLE


Accessory



LES09

- Product description**
- \_ Housing for SLE
  - \_ Diameter: 35 mm
  - \_ Material: Lexan Resin 943
  - \_ M3 screws with flat head, max. head diameter of 6 mm and max. torque for fixing is 0.5 Nm

**Website**  
<http://www.tridonic.com/28003024>



SLE G7 HOUSING LES09

| Ordering data            |                |                |                |
|--------------------------|----------------|----------------|----------------|
| Type                     | Article number | Packaging, bag | Weight per pc. |
| SLE G7 HOUSING LES 09    | 28003024       | 500 pc(s).     | 0.002 kg       |
| SLE G7 HOUSING LES 13/15 | 28003026       | 500 pc(s).     | 0.002 kg       |

## 1. Standards

EN 62031  
 EN 62471  
 IEC 62717  
 IEC 61000-4-2  
 UL 8750 (for CLASS2 circuits and dry locations)

### 1.1 Glow wire test for housing variants

according to IEC 60695-2-11 with increased temperature of 850 °C passed.

### 1.2 Photometric code

Key for photometric code, e. g. 830 / 359

| 1 <sup>st</sup> digit | 2 <sup>nd</sup> + 3 <sup>rd</sup> digit | 4 <sup>th</sup> digit              | 5 <sup>th</sup> digit                         | 6 <sup>th</sup> digit                               |
|-----------------------|-----------------------------------------|------------------------------------|-----------------------------------------------|-----------------------------------------------------|
| Code                  | CRI                                     | Colour temperature in Kelvin x 100 | MacAdam after 25% of the lifetime (max.6000h) | Luminous flux after 25% of the lifetime (max.6000h) |
| 7                     | 70 – 79                                 |                                    |                                               | Code                                                |
| 8                     | 80 – 89                                 |                                    |                                               | 7                                                   |
| 9                     | ≥90                                     |                                    |                                               | 8                                                   |
|                       |                                         |                                    |                                               | 9                                                   |

### 1.3 Energy classification

| Type                                 | Colour temperature | Forward current | Energy classification | Energy consumption |
|--------------------------------------|--------------------|-----------------|-----------------------|--------------------|
| <b>SLE G7 09mm – Without housing</b> |                    |                 |                       |                    |
| SLE G7 09mm 1200lm 830 R ADV         | 3,100 K            | 350 mA          | D                     | 13 kWh / 1,000 h   |
| SLE G7 09mm 1200lm 840 R ADV         | 4,100 K            | 350 mA          | D                     | 13 kWh / 1,000 h   |
| SLE G7 09mm 1200lm 927 R ADV         | 2,700 K            | 350 mA          | E                     | 13 kWh / 1,000 h   |
| SLE G7 09mm 1200lm 930 R ADV         | 3,100 K            | 350 mA          | E                     | 13 kWh / 1,000 h   |
| SLE G7 09mm 1200lm 940 R ADV         | 4,100 K            | 350 mA          | E                     | 13 kWh / 1,000 h   |
| <b>SLE G7 13mm – Without housing</b> |                    |                 |                       |                    |
| SLE G7 13mm 3000lm 827 R ADV         | 2,700 K            | 500 mA          | D                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 830 R ADV         | 3,100 K            | 500 mA          | D                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 835 R ADV         | 3,500 K            | 500 mA          | D                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 840 R ADV         | 4,100 K            | 500 mA          | D                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 927 R ADV         | 2,700 K            | 500 mA          | E                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 930 R ADV         | 3,100 K            | 500 mA          | E                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 935 R ADV         | 3,500 K            | 500 mA          | E                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 940 R ADV         | 4,100 K            | 500 mA          | E                     | 18 kWh / 1,000 h   |
| <b>SLE G7 15mm – Without housing</b> |                    |                 |                       |                    |
| SLE G7 15mm 4000lm 827 R ADV         | 2,700 K            | 900 mA          | D                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 830 R ADV         | 3,100 K            | 900 mA          | D                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 840 R ADV         | 4,100 K            | 900 mA          | D                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 927 R ADV         | 2,700 K            | 900 mA          | E                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 930 R ADV         | 3,100 K            | 900 mA          | E                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 940 R ADV         | 4,100 K            | 900 mA          | E                     | 32 kWh / 1,000 h   |
| <b>SLE G7 17mm – Without housing</b> |                    |                 |                       |                    |
| SLE G7 17mm 5000lm 827 R ADV         | 2,700 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 830 R ADV         | 3,100 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 835 R ADV         | 3,500 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 840 R ADV         | 4,100 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 927 R ADV         | 2,700 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 930 R ADV         | 3,100 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 935 R ADV         | 3,500 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 940 R ADV         | 4,100 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |

| Type                                                             | Colour temperature | Forward current | Energy classification | Energy consumption |
|------------------------------------------------------------------|--------------------|-----------------|-----------------------|--------------------|
| <b>SLE G7 21mm – Without housing</b>                             |                    |                 |                       |                    |
| SLE G7 21mm 6000lm 827 R ADV                                     | 2,700 K            | 1,400 mA        | D                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 830 R ADV                                     | 3,100 K            | 1,400 mA        | D                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 840 R ADV                                     | 4,100 K            | 1,400 mA        | D                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 927 R ADV                                     | 2,700 K            | 1,400 mA        | E                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 930 R ADV                                     | 3,100 K            | 1,400 mA        | E                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 940 R ADV                                     | 4,100 K            | 1,400 mA        | D                     | 50 kWh / 1,000 h   |
| <b>SLE G7 13mm – With housing</b>                                |                    |                 |                       |                    |
| SLE G7 13mm 3000lm 830 H ADV                                     | 3,100 K            | 500 mA          | D                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 840 H ADV                                     | 4,100 K            | 500 mA          | D                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 927 H ADV                                     | 2,700 K            | 500 mA          | E                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 930 H ADV                                     | 3,100 K            | 500 mA          | E                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 935 H ADV                                     | 3,500 K            | 500 mA          | E                     | 18 kWh / 1,000 h   |
| SLE G7 13mm 3000lm 940 H ADV                                     | 4,100 K            | 500 mA          | E                     | 18 kWh / 1,000 h   |
| <b>SLE G7 15mm – With housing</b>                                |                    |                 |                       |                    |
| SLE G7 15mm 4000lm 830 H ADV                                     | 3,100 K            | 900 mA          | D                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 840 H ADV                                     | 4,100 K            | 900 mA          | D                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 930 H ADV                                     | 3,100 K            | 900 mA          | E                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 940 H ADV                                     | 4,100 K            | 900 mA          | E                     | 32 kWh / 1,000 h   |
| <b>SLE G7 17mm – With housing</b>                                |                    |                 |                       |                    |
| SLE G7 17mm 5000lm 827 H ADV                                     | 2,700 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 830 H ADV                                     | 3,100 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 835 H ADV                                     | 3,500 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 840 H ADV                                     | 4,100 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 927 H ADV                                     | 2,700 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 930 H ADV                                     | 3,100 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 935 H ADV                                     | 3,500 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 940 H ADV                                     | 4,100 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| <b>SLE G7 21mm – With housing</b>                                |                    |                 |                       |                    |
| SLE G7 21mm 6000lm 827 H ADV                                     | 2,700 K            | 1,400 mA        | D                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 830 H ADV                                     | 3,100 K            | 1,400 mA        | D                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 840 H ADV                                     | 4,100 K            | 1,400 mA        | D                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 927 H ADV                                     | 2,700 K            | 1,400 mA        | E                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 930 H ADV                                     | 3,100 K            | 1,400 mA        | E                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 940 H ADV                                     | 4,100 K            | 1,400 mA        | E                     | 50 kWh / 1,000 h   |
| <b>SLE G7 15mm – With housing and thermal interface material</b> |                    |                 |                       |                    |
| SLE G7 15mm 4000lm 830 H ADV T                                   | 3,100 K            | 900 mA          | D                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 840 H ADV T                                   | 4,100 K            | 900 mA          | D                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 930 H ADV T                                   | 3,100 K            | 900 mA          | E                     | 32 kWh / 1,000 h   |
| SLE G7 15mm 4000lm 940 H ADV T                                   | 4,100 K            | 900 mA          | E                     | 32 kWh / 1,000 h   |
| <b>SLE G7 17mm – With housing and thermal interface material</b> |                    |                 |                       |                    |
| SLE G7 17mm 5000lm 830 H ADV T                                   | 3,100 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 840 H ADV T                                   | 4,100 K            | 1,050 mA        | D                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 930 H ADV T                                   | 3,100 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 935 H ADV T                                   | 3,500 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| SLE G7 17mm 5000lm 940 H ADV T                                   | 4,100 K            | 1,050 mA        | E                     | 38 kWh / 1,000 h   |
| <b>SLE G7 21mm – With housing and thermal interface material</b> |                    |                 |                       |                    |
| SLE G7 21mm 6000lm 830 H ADV T                                   | 3,100 K            | 1,400 mA        | D                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 840 H ADV T                                   | 4,100 K            | 1,400 mA        | D                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 930 H ADV T                                   | 3,100 K            | 1,400 mA        | E                     | 50 kWh / 1,000 h   |
| SLE G7 21mm 6000lm 940 H ADV T                                   | 4,100 K            | 1,400 mA        | E                     | 50 kWh / 1,000 h   |

Energy label and further information at [www.tridonic.com](http://www.tridonic.com) in the certificates tab of the corresponding product page and at the EPREL data base <https://eprel.ec.europa.eu/>

## 2. Thermal details

### 2.1 tp point, ambient temperature and lifetime


The temperature at tp reference point is crucial for the light output and lifetime of a LED product.

For SLE G7 a tp temperature of 65 °C has to be complied in order to achieve an optimum between heat sink requirements, light output and lifetime.

Compliance with the maximum permissible reference temperature at the tp point must be checked under operating conditions in a thermally stable state. The maximum value must be determined under worst-case conditions for the relevant application.

The tc and tp temperature of LED modules from Tridonic are measured at the same reference point.

To check the tc / tp temperature, the temperature sensor has to be mounted on the PCB at the marked position as stated in the drawing.



### 2.2 Storage and humidity


|                     |                |
|---------------------|----------------|
| storage temperature | -30 ... +80 °C |
|---------------------|----------------|

Operation only in non condensing environment.


Humidity during processing of the module should be between 0 to 85 %.

### 2.3 Derating curves


#### SLE G7 09mm 1200lm xx0 advanced




#### SLE G7 13mm 3000lm xx0 advanced




#### SLE G7 15mm 4000lm xx0 advanced



#### SLE G7 17mm 5000lm xx0 advanced



#### SLE G7 21mm 6000lm xx0 advanced



### 2.4 Thermal design and heat sink

The rated life of LED products depends to a large extent on the temperature. If the permissible temperature limits are exceeded, the life of the SLE G7 will be greatly reduced or the SLE G7 may be destroyed.

## 2.5 Heat sink values

SLE G7 09mm 1200lm xxx ADV

| ta    | tp    | Operating current | R <sub>th, hs-a</sub> |
|-------|-------|-------------------|-----------------------|
| 25 °C | 65 °C | 250 mA            | 4.6 K/W               |
| 35 °C | 65 °C | 250 mA            | 3.4 K/W               |
| 45 °C | 65 °C | 250 mA            | 2.2 K/W               |
| 25 °C | 65 °C | 350 mA            | 3.1 K/W               |
| 35 °C | 65 °C | 350 mA            | 2.3 K/W               |
| 45 °C | 65 °C | 350 mA            | 1.5 K/W               |
| 25 °C | 65 °C | 500 mA            | 2.1 K/W               |
| 35 °C | 65 °C | 500 mA            | 1.6 K/W               |
| 45 °C | 65 °C | 500 mA            | 1.0 K/W               |

SLE G7 13mm 3000lm xxx ADV

| ta    | tp    | Operating current | R <sub>th, hs-a</sub> |
|-------|-------|-------------------|-----------------------|
| 25 °C | 65 °C | 350 mA            | 3.4 K/W               |
| 35 °C | 65 °C | 350 mA            | 2.6 K/W               |
| 45 °C | 65 °C | 350 mA            | 1.7 K/W               |
| 25 °C | 65 °C | 500 mA            | 2.3 K/W               |
| 35 °C | 65 °C | 500 mA            | 1.7 K/W               |
| 45 °C | 65 °C | 500 mA            | 1.2 K/W               |
| 25 °C | 65 °C | 900 mA            | 1.2 K/W               |
| 35 °C | 65 °C | 900 mA            | 0.9 K/W               |
| 45 °C | 65 °C | 900 mA            | 0.6 K/W               |

SLE G7 15mm 4000lm xxx ADV

| ta    | tp    | Operating current | R <sub>th, hs-a</sub> |
|-------|-------|-------------------|-----------------------|
| 25 °C | 65 °C | 500 mA            | 2.4 K/W               |
| 35 °C | 65 °C | 500 mA            | 1.8 K/W               |
| 45 °C | 65 °C | 500 mA            | 1.2 K/W               |
| 25 °C | 65 °C | 900 mA            | 1.3 K/W               |
| 35 °C | 65 °C | 900 mA            | 1.0 K/W               |
| 45 °C | 65 °C | 900 mA            | 0.6 K/W               |
| 25 °C | 65 °C | 1,200 mA          | 0.9 K/W               |
| 35 °C | 65 °C | 1,200 mA          | 0.7 K/W               |
| 45 °C | 65 °C | 1,200 mA          | 0.5 K/W               |

SLE G7 17mm 5000lm xxx ADV

| ta    | tp    | Operating current | R <sub>th, hs-a</sub> |
|-------|-------|-------------------|-----------------------|
| 25 °C | 65 °C | 500 mA            | 2.3 K/W               |
| 35 °C | 65 °C | 500 mA            | 1.7 K/W               |
| 45 °C | 65 °C | 500 mA            | 1.1 K/W               |
| 25 °C | 65 °C | 1,050 mA          | 1.0 K/W               |
| 35 °C | 65 °C | 1,050 mA          | 0.7 K/W               |
| 45 °C | 65 °C | 1,050 mA          | 0.4 K/W               |
| 25 °C | 65 °C | 1,400 mA          | 0.7 K/W               |
| 35 °C | 65 °C | 1,400 mA          | 0.5 K/W               |
| 45 °C | 65 °C | 1,400 mA          | 0.3 K/W               |

SLE G7 21m 6000lm xxx ADV

| ta    | tp    | Operating current | R <sub>th, hs-a</sub> |
|-------|-------|-------------------|-----------------------|
| 25 °C | 65 °C | 700 mA            | 1.6 K/W               |
| 35 °C | 65 °C | 700 mA            | 1.2 K/W               |
| 45 °C | 65 °C | 700 mA            | 0.8 K/W               |
| 25 °C | 65 °C | 1,400 mA          | 0.7 K/W               |
| 35 °C | 65 °C | 1,400 mA          | 0.5 K/W               |
| 45 °C | 65 °C | 1,400 mA          | 0.3 K/W               |
| 25 °C | 65 °C | 2,000 mA          | 0.5 K/W               |
| 35 °C | 65 °C | 2,000 mA          | 0.3 K/W               |
| 45 °C | 65 °C | 2,000 mA          | 0.2 K/W               |

## Notes

The actual cooling can differ because of the material, the structural shape, outside influences and the installation situation. A thermal connection between SLE G7 and heat sink with heat-conducting paste or heat conducting adhesive film is absolutely necessary.

Additionally the SLE G7 has to be fixed on the heat sink with M3 screws to optimise the thermal connection.

Use of thermal interface material with thermal conductivity of  $\lambda > 1 \text{ W/mK}$  and layer thickness of interface material with max. 50  $\mu\text{m}$  or a similar interface material where the quotient of layer thickness and thermal conductivity  $b < 50 \text{ } \mu\text{mmK/W}$ .

The SLE G7 H ADV T modules will be delivered with thermal interface foil of type GRAFTECH HT-1205A.

The bottom side of the thermal pad is glued to the module, the upper side is not adhesive. This makes it easier to position the module when it is connected to the heat sink.



The thermal pad is an integral part of the LED module and must not be confused with a protective foil. The thermal pad must not be pulled off!

For further information about the thermal interface foil please refer to the data sheet of the product GRAFTECH HT-1205A.

### 3. Installation / wiring

#### 3.1 Electrical supply/choice of LED driver

SLE G7 from Tridonic are not protected against overvoltages, overcurrents, overloads or short-circuit currents. Safe and reliable operation can only be guaranteed in conjunction with a LED driver which complies with the relevant standards. The use of LED drivers from Tridonic in combination with SLE G7 guarantees the necessary protection for safe and reliable operation.

If a LED driver other than Tridonic is used, it must provide the following protection:

- Short-circuit protection
- Overload protection
- Overtemperature protection



SLE G7 must be supplied by a constant current LED driver. Operation with a constant voltage LED driver will lead to an irreversible damage of the module. Wrong polarity can damage the SLE G7.



SLE G7 must not be operated with nonSELV LED driver.




SLE G7 are basic insulated up to 60 V SELV against ground and can be mounted directly on earthed metal parts of the luminaire. If the max. output voltage of the LED driver (also against earth) is above 60 V SELV, an additional insulation between LED module and heat sink is required (for example by insulated thermal pads) or by a suitable luminaire construction.


At voltages > 60 V an additional protection against direct touch (test finger) to the light emitting side of the module has to be guaranteed. This is typically achieved by means of a non removable light distributor over the module.

#### 3.2 Wiring

##### Wiring with housing (LES13 and LES15)




##### Wiring with housing (LES17 and LES21)




#### Wiring without housing


##### LES09



##### LES13





##### LES15





LES17 + LES21


**Wiring example****3.3 Wiring type and cross section for housing variants**

For wiring use solid wire from 0.5 to 0.75 mm<sup>2</sup> or stranded wire with soldered ends of 0.5 mm<sup>2</sup>.

For the push-wire connection you have to strip the insulation (6 – 7 mm).

Loosen wire through twisting and pulling.

wire preparation:

**3.4 Mounting instruction**

SLE G7 from Tridonic which have to be installed on a heat sink have to be connected with heat-conducting paste or heat conducting adhesive film and fixed with M3 screws.

The fixing/cooling surface must be cleaned by removing all dirt, dust and grease before installing the LED modules.

None of the components of the SLE G7 (substrate, LED, electronic components etc.) may be exposed to tensile or compressive stresses.



Max. torque for fixing: 0.3 Nm (LES9, LES13, LES15)  
0.5 Nm (LES17, LES21)

The LED modules are mounted with 2 screws per module. In order not to damage the modules only rounded head screws and an additional plastic flat washer (notice working temperature) or rounded head screw with collar (ISO 7380-2) with head diameter ≤ 6.9 mm must be used for LED modules without housing (for LES13, LES15).

Chemical substance may harm the LED module. Chemical reactions could lead to colour shift, reduced luminous flux or a total failure of the module caused by corrosion of electrical connections.



Materials which are used in LED applications (e.g. sealings, adhesives) must not produce dissolver gas. They must not be condensation curing based, acetate curing based or contain sulfur, chlorine or phthalate.

Avoid corrosive atmosphere during usage and storage.

**3.5 EOS/ESD safety guidelines**

The device / module contains components that are sensitive to electrostatic discharge and may only be installed in the factory and on site if appropriate EOS/ESD protection measures have been taken. No special measures need be taken for devices/modules with enclosed casings (contact with the pc board not possible), just normal installation practice.

For further information for EOS/ESD safety guidelines and the ESD classification please refer to the brochure entitled <http://www.tridonic.com/esd-protection>.

## 4. Lifetime

### 4.1 Lifetime, lumen maintenance and failure rate

The light output of an LED module decreases over the lifetime, this is characterized with the L value. L70 means that the LED module will give 70 % of its initial luminous flux. This value is always related to the number of operation hours and therefore defines the lifetime of an LED module.

As the L value is a statistical value and the lumen maintenance may vary over the delivered LED modules. The B value defines the amount of modules which are below the specific L value, e.g. L70B10 means 10 % of the LED modules are below 70 % of the initial luminous flux, respectively 90 % will be above 70 % of the initial value.

In addition the percentage of failed modules (fatal failure) is characterized by the C value.

The F value is the combination of the B and C value. That means for F degradation and complete failures are considered, e.g. L70F10 means 10 % of the LED modules may fail or be below 70 % of the initial luminous flux.

### 4.2 Lumen maintenance

Lifetime declarations are informative and represent no warranty claim. Preliminary calculated lifetime data until LM80 test reports are available

#### SLE G7 09mm 1200lm ADV

| Operating current | tp temperature | L90 / F10 | L90 / F50 | L80 / F10 | L80 / F50 | L70 / F10 | L70 / F50 |
|-------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 250 mA            | 65 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 26,000 h  | 37,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 350 mA            | 65 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 13,000 h  | 20,000 h  | 31,000 h  | 49,000 h  | 51,000 h  | >55,000 h |
| 500 mA            | 65 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 13,000 h  | 20,000 h  | 31,000 h  | 49,000 h  | 51,000 h  | >55,000 h |

#### SLE G7 13mm 3000lm ADV

| Operating current | tp temperature | L90 / F10 | L90 / F50 | L80 / F10 | L80 / F50 | L70 / F10 | L70 / F50 |
|-------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 350 mA            | 65 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 26,000 h  | 37,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 500 mA            | 65 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 26,000 h  | 37,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 900 mA            | 65 °C          | 37,000 h  | 51,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 37,000 h  | 51,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 13,000 h  | 20,000 h  | 31,000 h  | 49,000 h  | 50,000 h  | >55,000 h |

#### SLE G7 15mm 4000lm ADV

| Operating current | tp temperature | L90 / F10 | L90 / F50 | L80 / F10 | L80 / F50 | L70 / F10 | L70 / F50 |
|-------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 500 mA            | 65 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 26,000 h  | 37,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 900 mA            | 65 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 26,000 h  | 37,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 1,200 mA          | 65 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 13,000 h  | 20,000 h  | 31,000 h  | 49,000 h  | 51,000 h  | >55,000 h |

**SLE G7 17mm 5000lm ADV**

| Operating current | tp temperature | L90 / F10 | L90 / F50 | L80 / F10 | L80 / F50 | L70 / F10 | L70 / F50 |
|-------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 500 mA            | 65 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 26,000 h  | 37,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 1,050 mA          | 65 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 26,000 h  | 37,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 1,400 mA          | 65 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 13,000 h  | 20,000 h  | 31,000 h  | 50,000 h  | 51,000 h  | >55,000 h |

**SLE G7 21mm 6000lm ADV**

| Operating current | tp temperature | L90 / F10 | L90 / F50 | L80 / F10 | L80 / F50 | L70 / F10 | L70 / F50 |
|-------------------|----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| 700 mA            | 65 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 26,000 h  | 37,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 1,400 mA          | 65 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | 50,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 26,000 h  | 37,000 h  | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
| 2,000 mA          | 65 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 85 °C          | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h | >55,000 h |
|                   | 105 °C         | 13,000 h  | 20,000 h  | 31,000 h  | 50,000 h  | 51,000 h  | >55,000 h |

## 5. Electrical values

### 5.1 Declaration of electrical parameters

I<sub>rated</sub> ... Nominal operating current the module is designed for.


I<sub>max</sub> ... Max. permissible continuous operating current incl. The tolerances of the LED driver.

Max. permissible LF current ripple ... Max. output current of the LED driver incl. Tolerances and LF current ripple must not exceed this value.


Max. permissible peak current ... The max. output peak current of the LED driver must not exceed this value.

### 5.2 Typ. forward voltage vs. forward current


**SLE G7 09mm 1200lm xxx ADV**




**SLE G7 15mm 4000lm xxx ADV**





**SLE G7 13mm 3000lm xxx ADV**



**SLE G7 17mm 5000lm xxx ADV**



**SLE G7 21mm 6000lm xxx ADV****5.3 Forward voltage vs. tp temperature**

The diagrams based on statistic values.  
The real values can be different.

## 6. Photometric characteristics


### 6.1 Coordinates and tolerances according to CIE 1931 and colour rendering

The specified colour coordinates are measured integral after a settling time of 100 ms. The current impuls depends on the module type. The ambient temperature of the measurement is  $t_a = 25^\circ\text{C}$ . The measurement tolerance of the colour coordinates are  $\pm 0.01$ .

| Module type                | Current impulse |
|----------------------------|-----------------|
| SLE G7 09mm 1200lm xxx ADV | 350 mA          |
| SLE G7 13mm 3000lm xxx ADV | 500 mA          |
| SLE G7 15mm 4000lm xxx ADV | 900 mA          |
| SLE G7 17mm 5000lm xxx ADV | 1,050 mA        |
| SLE G7 21mm 6000lm xxx ADV | 1,400 mA        |


#### 2,700 K – CRI80

|        | x0     | y0     |
|--------|--------|--------|
| Centre | 0.4599 | 0.4106 |




MacAdam ellipse: 3SDCM


| TM30 |    | CRI |    |
|------|----|-----|----|
| Rf   | Rg | Ra  | R9 |
| 82   | 92 | 81  | 12 |



Colour vector graphic




— Reference source  
— Test source




**2,700 K – CRI90**

|        | x0     | y0     |
|--------|--------|--------|
| Centre | 0.4599 | 0.4106 |




MacAdam ellipse: 3SDCM


| TM30 |    | CRI |    |
|------|----|-----|----|
| Rf   | Rg | Ra  | R9 |
| 89   | 97 | 91  | 56 |



Colour vector graphic




— Reference source  
— Test source




**3,100 K – CRI80**

|        | x0     | y0     |
|--------|--------|--------|
| Centre | 0.4300 | 0.4016 |




MacAdam ellipse: 3SDCM


| TM30 |    | CRI |    |
|------|----|-----|----|
| Rf   | Rg | Ra  | R9 |
| 84   | 96 | 83  | 8  |



## Colour vector graphic




— Reference source  
— Test source






**3,100 K – CRI90**

|        | x0     | y0     |
|--------|--------|--------|
| Centre | 0.4300 | 0.4016 |




MacAdam ellipse: 3SDCM


| TM30 |    | CRI |    |
|------|----|-----|----|
| Rf   | Rg | Ra  | R9 |
| 90   | 98 | 92  | 59 |



Colour vector graphic




— Reference source  
— Test source




**3,500 K – CRI80**

|        | x0     | y0     |
|--------|--------|--------|
| Centre | 0.4053 | 0.3907 |




MacAdam ellipse: 3SDCM


| TM30 |    | CRI |    |
|------|----|-----|----|
| Rf   | Rg | Ra  | R9 |
| 82   | 91 | 85  | 22 |



Colour vector graphic




— Reference source  
— Test source




**3,500 K – CRI90**

|        | x0     | y0     |
|--------|--------|--------|
| Centre | 0.4053 | 0.3907 |




MacAdam ellipse: 3SDCM


| TM30 |    | CRI |    |
|------|----|-----|----|
| Rf   | Rg | Ra  | R9 |
| 90   | 98 | 94  | 70 |



## Colour vector graphic




— Reference source  
— Test source




**4,100 K – CRI80**

|        | x0     | y0     |
|--------|--------|--------|
| Centre | 0.3761 | 0.3740 |




MacAdam ellipse: 3SDCM


| TM30 |    | CRI |    |
|------|----|-----|----|
| Rf   | Rg | Ra  | R9 |
| 82   | 95 | 83  | 5  |



Colour vector graphic




— Reference source  
— Test source




**4,100 K – CRI90**

|        | x0     | y0     |
|--------|--------|--------|
| Centre | 0.3761 | 0.3740 |




MacAdam ellipse: 3SDCM


| TM30 |     | CRI |    |
|------|-----|-----|----|
| Rf   | Rg  | Ra  | R9 |
| 90   | 100 | 91  | 70 |



Colour vector graphic




— Reference source  
— Test source




## 6.2 Light distribution

The optical design of the SLE product line ensures optimum homogeneity for the light distribution.




## 6.3 Relative luminous flux vs. tp temperature




## 6.4 Relative luminous flux vs. operating current


SLE G7 09mm 1200lm xxx ADV




SLE G7 17mm 5000lm xxx ADV




SLE G7 13mm 3000lm xxx ADV



SLE G7 21mm 6000lm xxx ADV



SLE G7 15mm 4000lm xxx ADV



## 7. Miscellaneous

### 7.1 Additional information

Additional technical information at [www.tridonic.com](http://www.tridonic.com) → Technical Data

Guarantee conditions at [www.tridonic.com](http://www.tridonic.com) → Services

Lifetime declarations are informative and represent no warranty claim.

Colour rendering information are typical values and represent no warranty claim.