

Certifications / Certificazioni



Technical info / Info tecniche



Other color temperatures and CRI available on request. Values marked with an asterisk (*) are measurement values that refer to an ambient temperature of 25°C unless otherwise specified.

Over time, the luminous flux undergoes an inevitable decrease due to technology. A.A.G. Stucchi reserves the right to make technical changes without notice.

Other color temperatures and CRI available on request. Values marked with an asterisk (*) are measurement values that refer to an ambient temperature of 25°C unless otherwise specified.

Over time, the luminous flux undergoes an inevitable decrease due to technology. A.A.G. Stucchi reserves the right to make technical changes without notice.

SENZAFINE EVO FLAT UGR / SENZAFINE EVO FLAT UGR

PRODUCT CODE / CODICE PRODOTTO

M16300/W25-U-2

DESCRIPTION / DESCRIZIONE

48V linear light module. For 9500 tracks. EVO / MULTISYSTEM®. Aluminum body. Polycarbonate UGR reflector. Polyamide cover. L(mm): 300.

48V linear light module. For 9500 tracks. EVO / MULTISYSTEM®. Aluminum body. Polycarbonate UGR reflector. Polyamide cover. L(mm): 300.

TECHNICAL DATA / DATI TECNICI

Application ON TRACK

Real Flux(lm) 293.4

Nominal Flux(lm) 440.12

Real Power(W) 4.9

Efficiency(lm / W) 59.9

LED source LED

Colour Temperature(K) 3000

CRI 90

MacAdam ≤ 3

Beam Angle 65,0°x65,8°

UGR

<22	X=4H Y=8H	S=0.25H
	Reflection factors:	70/50/20
	UGR transversal:	18.8
	UGR axial:	19.5

Lifetime(Khr) >50Khr L90B10

Driver DALI

VF ~ 15

I LED(mA) 300

L(mm) 300



Weight(g) 49

Materials Polycarbonate UGR reflector + polyamide body

Colour Bianco

Mounting Mechanical

Packaging Tube



Room (m): 4x4x3h H luminaire (m): 2.5 Ref. surface: floor