



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Junction box for resin filling 4 ways D7-13.5 IP66/IP68

Code: **THA.219.A1A**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Joint connector (re-usable/re-accessible)
Product configuration	Junction box (with resin-gel)
Colour	Black (Plastic components) - Techno green (Rubber components)
Overall dimensions (mm)	121.0 x 64.5 x 28.0
Inner dimensions (mm)	50.0 x 40.0 x 24.0

ELECTRIC DATA

No. connected cables	4
----------------------	---

CONNECTION DATA

Main cable sheath stripping length 30.00
(mm)

Branch cable sheath str
length (mm)

Reccomended types of c

Cable diameter MIN (mr

Cable diameter MAX (m

Tightening torque of nut
gland

Tightening torque of Lid
screws



ENVIRONMENT CO

IP rating

IK rating

Salt Mist

Salt mist test : EN60068-2-11:2000

Ambient temperature MIN/MAX
(According to
EN61984/EN60998/EN62444)

-40°C/+60°C

MATERIALS

Exterior body

PA66 UL94 V2

O Rings

TPE

Gaskets

TPE

Material property

Halogen Free - Silicone Free

Lid/Fixing screws

Stainless Steel

PRODUCT COMPLIANCES

IEC Approvals

EN 60529:1991 - EN 60998-1:2004

COMMERCIAL DATA

EAN

8057457091831

Packing method

Bulk packed (OEM)

Type of packaging

Box

Pieces/box (pcs)

100

Weight per Piece (gr)

71.30

Overall dimensions of box (mm)

600 x 270 x 400

Corresponding code in KIT

THR.219.AOA

Custom tariff number

85369010

Country of origin

ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Type	Size
 606001800_IST_TH209_TH219.pdf	PDF	1.26 MB

DRAWINGS

Drawings:

File	Type	Size
 THA.219.A1A.pdf	PDF	239.59 KB

MARKETING DOCUMENTS

Please login to access this data.