



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

KIT Micro Plug and Socket Connector 2p Screw D3.5-7.9 IP66/IP68

Code: **THB.381.A2A.R**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Plug and Socket connector
Product configuration	Plug and Socket connector
Locking mechanism	Push Pull
Colour	Black (Plastic components) - Techno green (Rubber components)
Overall dimensions (mm)	Ø 14.0 x 53.0
Overall dimensions when mated together (mm)	Ø 14.0 x 90.0

ELECTRIC DATA

No. connected cables	2
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	10A AC/DC
Voltage rating (AC/DC)	500V AC (3V-60V DC)
Double insulated (Class II)	250V
Impulse withstand voltage	4kV
No. poles	2
Marking	1-2
Terminations	Screw
Terminations Thread/Tightening torque	M2 - 0.2 Nm

CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm ²)	0.25
Multi-stranded conductor cross-section without ferrule MAX (mm ²)	1.50
Conductor stripping length (mm)	10.00
Cable sheath stripping length (mm)	20.00
Recommened types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	3.50
Cable diameter MAX (mm)	7.90
Tightening torque of cable gland-connector	1 Nm
Tightening torque of nut-cable gland	1.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP66, IP68
	<i>*IP68 (30m/1h)</i>
Salt Mist	Salt mist test : EN60068-2-11:2000
Mating cycles	100 cycles
Ambient temperature MIN/MAX (According to EN61984/EN60998/EN62444)	-40°C/+125°C
Operating temperature MAX	+60°C
Proof Tracking Index (PTI)	PTI 175

MATERIALS

Connector	PA66 GF UL94 V0
Cable gland	PA66 GF UL94 V2
O Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals	EN 61984:2009 - EN 61535
---------------	--------------------------

COMMERCIAL DATA

EAN	8057457090131
Packing method	Individually packed (KIT)
Type of packaging	Blister
Pieces/kit (pcs)	1
Pieces/box (pcs)	50
Weight per Piece (gr)	37.70
Overall dimensions of box (mm)	300 x 200 x 160
Corresponding code in Box	THB.381.A2A - THB.381.B2A
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Type	Size
 606002032_Install sheet_TH381_web.pdf	PDF	1.13 MB
 Gasket compatibility TH381-TH395.pdf	PDF	404.24 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.
