



PRODUCT CODE / CODICE PRODOTTO

9409-4-DRI/W-S2-N-1

DESCRIPTION / DESCRIZIONE

ASYMMETRICAL ADAPTER WITH SINGLE LOCKING TAB, 4 CONDUCTORS (3 PHASES + N), WITH PHASE SELECTOR, WITH INTEGRATED DRIVER

ADATTATORE ASIMMETRICO CON MONOLEVA DI AGGANCIO MANUALE, A 4 CONDUTTORI (3 FASI+N), CON SELETTORE DI FASE, CON DRIVER INTEGRATO

TECHNICAL DATA / DATI TECNICI

Frequency:	50/60Hz
<i>Frequency:</i>	
Rated current and voltage:	0.22A / 220/240V
<i>Rated current and voltage:</i>	
Max. voltage (output):	59V dc
<i>Max. voltage (output):</i>	

FEATURES / CARATTERISTICHE

Materials:	Polycarbonate body; Copper alloy contacts
<i>Materiali:</i>	Corpo in policarbonato; Contatti in lega di rame
Available colours:	White RAL 9010
<i>Colori disponibili:</i>	Bianco RAL 9010
Fastening:	Insert with cam rotation
<i>Fissaggio:</i>	Ad innesto con rotazione camme
Weight:	142,3 g
<i>Peso:</i>	
Max load:	50 N
<i>Carico:</i>	
Maximum torque:	2,5Nm
<i>Massimo momento torcente:</i>	
Not compatible with:	9000...TR
<i>Non compatibile con:</i>	

Information / Informazioni



Certifications / Certificazioni



WIRING / WIRING



automatic clamp with 1 hole
Serrafilo automatico ad 1 foro



0,2-0,5

Section of stranded and flexible conductor (mm²)
Sezione conduttore cordato e flessibile (mm²)

ACCESSORIES / ACCESSORI



S-9009/M...-SC



S-9009/M...-FI

Specifications / Specifiche

T_A
35°C

Notes / Note

Selectable powers/currents via dipswitch (16 combinations) 12.6W (300mA) – 40W (1050mA)

Potenze/currenti selezionabili mediante dipswitch (16 combinazioni) 12.6W (300mA) – 40W (1050mA)