

The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

High performance

M25 Nero

CE UK
CA



Potential improvements

al data contained in this

GENERAL INFORMATION

Type of installation	Cable fixing system (Cable glands)
Product configuration	Panel-mount connector (rear nut)
	<i>*Fixing nut to be ordered separately</i>
Colour	Grey RAL7035 (Plastic components) - Black (Rubber components)
Overall dimensions (mm)	Ø 31.5 x 35.5 (outer thread 10.0)
Panel nut thread	M25
Panel thickness (mm)	5.00
Connector shape	Straight

CONNECTION DATA

Cable diameter MIN (mm)	11.00
Cable diameter MAX (mm)	17.00
Tightening torque of panel nut	5.0 Nm
Tightening torque of nut-cable gland	5.0 Nm

ENVIRONMENT CONDITIONS

IP rating	IP66, IP68, IP69
	<i>*IP68 (10m/30min)</i>
IK rating	IK07
Salt Mist	Salt mist test : EN60068-2-11:2000
Ambient temperature MIN/MAX (According to EN61984/EN60998/EN62444)	-40°C/+100°C

MATERIALS

Cable gland	PA6 UL94 V0
O Rings	CR
Gaskets	CR
Material property	Silicone Free

PRODUCT COMPLIANCES

UL/CSA Approvals	UL514B/C22.2 No.18.3-12
Other approvals	EN 62444:2013

COMMERCIAL DATA

Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	50
Custom tariff number	85369010

APPROVALS

Please login to access this data.

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.
