
A.A.G. STUCCHI s.r.l. u.s
Via IV Novembre 30/32
23854 Olginate (LC)
www.aagstucchi.it
info@aagstucchi.it



SENZAFINE HE MAIN VOLTAGE WALLWASHER / *SENZAFINE HE MAIN VOLTAGE WALLWASHER*


PRODUCT CODE / *CODICE PRODOTTO*

M14500/BG8-WL-2-MV

DESCRIPTION / *DESCRIZIONE*

230V linear light module. For 9000/9000A ONETRACK™ range tracks. Wallwasher reflector. L(mm): 628.

230V linear light module. For 9000/9000A ONETRACK™ range tracks. Wallwasher reflector. L(mm): 628.



Certifications / *Certificazioni*

Technical info / *Info tecniche*

220..240Vac 50..60Hz | IP20 | RG1 unlimited

Other colour temperatures and CRI available upon request. All values marked with an (*) are rated values. Unless stated otherwise, the values apply to an ambient temperature of 25°C.
Luminous flux is subject to a normal technology drop over time. A.A.G. Stucchi reserves the right to make technical changes without prior notice. Real power: ±10% tolerance

Other colour temperatures and CRI available upon request. All values marked with an (*) are rated values. Unless stated otherwise, the values apply to an ambient temperature of 25°C.
Luminous flux is subject to a normal technology drop over time. A.A.G. Stucchi reserves the right to make technical changes without prior notice. Real power: ±10% tolerance

TECHNICAL DATA / *DATI TECNICI*

Application	ON TRACK
Real Flux(lm)	944.47
Nominal Flux(lm)	1295.8
Real Power(W)	12.9
Efficiency(lm / W)	73.2
LED source	LED
Colour Temperature(K)	2700
CRI	90
MacAdam	≤ 3
Beam Angle	43,5°x93,2°
UGR	<30 — X=4H Y=8H S=0.25H; Reflection factors: 70/50/20; UGR transversal: 0; UGR axial: 27.7
Lifetime(Khr)	>60Khr L90B5
Driver	DALI 2
VF	~ 16
I LED(mA)	600mA
L(mm)	628
Weight(g)	475
Materials	Aluminium body + PMMA lenses + polycarbonate reflectors
Colour	Nero
Mounting	Mechanical
Packaging	Cardboard box

